

**NOTES:**  
 1. MINIMUM 38x189 JOIST REQUIRED FOR GUARD SUPPORT

CONTINUOUS 38x140 TOP RAIL

38x38 PICKETS SECURED W/ 2-76mm SCREWS OR OTHER APPROVED GUARD SYSTEM

LESS THAN 100mm OPENING BETWEEN PICKETS & NO MEMBER OR ATTACHMENT BETWEEN 140mm & 900mm SHALL FACILITATE CLIMBING

4-#9 x76mm SCREWS BOTH SIDES OR 2-9.5mm THRU BOLTS C/W 32mm O.D. WASHERS

WOOD DECKING W/ 6mm GAPS PERPENDICULAR TO DECK JOIST FRAMING

WOOD JOIST

WOOD BEAM W/ PLYWOOD FILLER & 38x89 GUSSETS ON BOTH SIDES OF POST  
 76mm SCREWS OR 76x165 METAL POST & BEAM CONNECTOR

89x89 MIN. WOOD POST ANCHORED TO CONC. PIER W/ METAL SHOE & 12.7mm DIA BOLT SHOE ANCHORED MINIMUM 100mm INTO CONCRETE PIER

POURED CONCRETE PIER MIN. 1200mm BELOW GRADE ON UNDISTURBED SOIL,

SECTION 'A'

900mm

1500mm OR LESS


50mm MIN.

150mm MIN.

1200mm MIN.

UNDISTURBED SOIL

POOL



SEE STAIR DETAIL TACBOC SHEET D01c

PLAN



DETAIL  
 POOL DECK  
 JOISTS PARALLEL  
 PLAN & SECTION

PERMIT APPLICATION #

REVIEWED BY:

DATE:

DWG. NO.

X-19

July 2009